


Cartridge

223 Rem - 40 grain

Version 9.0

NOSLER®



223 Rem - 40 grain

22 Cal. (.224")

MAXIMUM SAAMI O.A.C.L.		2.260"	TESTED O.A.C.L.	B.C.	S.D.
Ballistic Tip® Lead-Free	BTLF	40gr. Spitzer	2.260"	0.220	0.114
Ballistic Tip® Varmint	BTV	40gr. Spitzer	2.260"	0.221	0.114
Varmageddon®	VMG	40gr. FB Tipped	2.225"	0.211	0.114
CASE TYPE:	Nosler		PRIMER TYPE	Rem 7 1/2	
CASE HOLDS:	29.2	Gr. WATER	BARREL Length/Make	24" Lilja	
			BARREL Twist	1-12"	
POWDER TYPE	POWDER CHG. GRS.	MUZZLE VEL. F.P.S.	LOAD DENSITY (VOLUME)		
Varget	27.0	MAX. 3383	100%		
	26.0	3247	96%		
	25.0 *	3111	93%		
W748 Most Accurate Powder Tested	28.0 * MAX.	3547	100%		
	27.0	3426	96%		
	26.0	3304	93%		
H322	25.0	MAX. 3570	93%		
	24.0	3437	89%		
	23.0 *	3304	85%		
RL7	23.5 * MAX.	3614	87%		
	22.5	3492	84%		
	21.5	3370	80%		
PP Varmint	29.0	MAX. 3642	100%		
	28.0	3476	97%		
	27.0 *	3311	93%		
H335	27.5 * MAX.	3681	96%		
	26.5	3544	92%		
	25.5	3406	89%		
IMR 4198	23.0	MAX. 3682	91%		
	22.0	3492	87%		
	21.0 *	3302	83%		
AA 2015	25.5	MAX. 3796	99%		
	24.5	3627	95%		
	23.5 *	3458	91%		
N120	23.5	MAX. 3810	98%		
	22.5	3677	94%		
	21.5 *	3543	90%		
Benchmark	28.0 * MAX.	3867	**		104%
	27.0	3738	100%		
	26.0	3609	96%		

All cartridge measurements are SAAMI maximum and due to variations from manufacturers actual measurements may vary

* Because Nosler, Inc. has no control over the actual components selected, the manner in which they are assembled or the condition of the firearm used, no responsibility, either expressed or implied is assumed for the use of this data.

In no event shall Nosler, Inc. be liable for any damages resulting from the use of this data.*

* = Most accurate load tested

** = Compressed load